Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL							
YEAR	ENGINE FAMILY 5CEXH0661MAU	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS 2	ECS & SPECIAL FEATURES	3
NGINE (L)	)	10.8	Diesel	Diesel	ННОО		
10.8			ENGINE MOI	DELS / CODES (ra	ated power, in	PCM, EGR, DDI, TC, CAC	
*				See Attachme	nt		
*				*			
*				*			
=not applicat =liter; hp=ho	ble; GVWR=gross vehicle prsepower; kw=kilowatt;	weight rating; 13 CC	R xyz=Title 13, California Code o	f Population 0		36.abc=Title 40. Code of Federal Population 2	
CNG/LNG	=compressed/liquefied na	tural gae: L BC-II-		" regulations, Sections	on xyz; 40 CFR 8	36.abc=Title 40. Code of Federal Regulation	

<sup>=</sup>not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc;

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.1 (urban bus) or 13 CCR 1956.8 (other than urban bus); 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.1 or 13 CCR 1956.8 are in parentheses.)

	N	NMHC NMHC		NOx		NMHC+NOx		CR 1956.1 or 13 CCR 1956.8 are in parentheses.)					
	FTP	EURO	FTP	EURO	FTP			co	1	PM	Н	СНО	
	0.5	0.5	*		- 1	EURO	FTP	EURO	FTP	EURO	FTP		
		T		<del></del>		<u> </u>	15.5	15.5	0.10	0.10		EURO	
T	0.2	0.1		<del>                                     </del>	2.3	2.3	*		•	*	<del></del> -	<u> </u>	
					2.0	2.1	0.8	0.4	0.10	1 000		<u> </u>	
0.625 /bhp-hr-grams per brake horsepower-hour; FTP=Federal Test			2.875		19.375		0.10 0.08			*			

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-021-0385-1 dated December 24, 2004.

Executed at El Monte, California on this

Allen Lyons, Chief

Mobile Source Operations Division

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; EB5=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; LMH HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty (prefix) = warm-up catalyst; DF=diesel particulate filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDIDDDI=indirect/direct diesel injection; TC/SC=turbo/super charger; CAC=charge air cooler; EGR=exhaust gas recirculation; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; (2004may26)